ENVIRONMENTAL PRODUCT DECLARATION

as per ISO 14025 and EN 15804+A1

Owner of the Declaration Kunda Nordic Tsement AS

Programme holder Institut Bauen und Umwelt e.V. (IBU

Publisher Institut Bauen und Umwelt e.V. (IBU)

Declaration number EPD-KNT-20200210-CAA1-EN

Issue date 11/12/2020 Valid to 10/12/2025

Portland Cement CEM I 52,5 R Kunda Nordic Tsement AS, HeidelbergCement Group



www.ibu-epd.com | https://epd-online.com





General Information

Kunda Nordic Tsement AS, HeidelbergCement Group

Programme holder

IBU – Institut Bauen und Umwelt e.V. Panoramastr. 1 10178 Berlin Germany

Declaration number

EPD-KNT-20200210-CAA1-EN

This declaration is based on the product category rules:

Cement, 07.2014 (PCR checked and approved by the SVR)

Issue date

11/12/2020

Valid to

10/12/2025

Man Athan
Dipl. Ing. Hans Peters

(chairman of Institut Bauen und Umwelt e.V.)

Dr. Alexander Röder

(Managing Director Institut Bauen und Umwelt e.V.))

Portland Cement CEM I 52,5 R

Owner of the declaration

Kunda Nordic Tsement AS Jaama 2, Kunda 44106 Estonia

Declared product / declared unit

1 metric t of CEM I 52,5 R

Scope:

This Environmental Product Declaration (EPD) covers the product life cycle stages A1-A3. It is valid for Portland Cement CEM I 52,5 R, manufactured by Kunda Nordic Tsement AS in the plant Kunda, Estonia in 2020. This analysis relies on transparent, plausible and documented basis data. All the model assumptions, which influence the results, are declared. The life cycle assessment is representative for the products introduced in the declaration for the given system boundaries.

The owner of the declaration shall be liable for the underlying information and evidence; the IBU shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

The EPD was created according to the specifications of *EN 15804+A1*. In the following, the standard will be simplified as *EN 15804*.

Verification

The standard *EN 15804* serves as the core PCR Independent verification of the declaration and data according to *ISO 14025:2010*

Schindle

internally

x e

externally

Angela Schindler
(Independent verifier)

Product

Information about the enterprise

Kunda Nordic Tsement AS is a company with the history of 150 years. Kunda Nordic Tsement produces constructional cements and crushed limestone. Kunda Nordic Tsement AS is a member of HeidelbergCement Group, which is the global market leader in aggregates and a prominent player in the fields of cement, concrete and other downstream activities, making it one of the world's largest manufacturers of building materials.

Product description/Product definition

Cement is a hydraulic binder. It consists of finelyground, non-metallic inorganic compounds. Cement is produced by grinding cement clinker and other main or minor constituents. When water is added to cement, a cement paste is formed, which sets and hardens through the hydration reactions. After hardening, it retains its strength and stability even under water. The declared product is a cement

conforming with the composition of Portland Cement CEM I 52.5 R manufactured by Kunda Nordic Tsement AS in the plant Kunda in 2020. The calculation is based on plant-specific data.

For the placing on the market of the product in the European Union/European Free Trade Association (EU/EFTA) (with the exception of Switzerland) Construction Product Regulation (EU) No 305/2011 applies. The product needs a declaration of performance taking into consideration *EN 197-1*, composition specification and conformity criteria for common cements and the CE-marking. For the application and use the respective national provisions apply.

Application

The application of cement has a large variety. It is mainly used as a binder for concrete and mortar. The application in concrete is regulated in *EN 206*.



According to this standard, general suitability is established for cement conforming to EN 197-1.

Technical Data

The declared cement corresponds to the 52.5 standard compressive strength class with high early strength development (R) in accordance with *EN 197-1*.

Constructional data

Name	Value	Unit
Strength class acc. to EN 197-1	52.5	N/mm ²

Performance data of the product in accordance with the declaration of performance with respect to its essential characteristics according to *EN 197*-

1, Composition specification and conformity criteria for common cements.

Base materials/Ancillary materials

Clinker: 95-100 %

Cement clinker is made of a raw material mixture that is added to the cement kiln and sintered at a temperature of 1400 °C. The basic materials for the

production of cement clinker consist of calcium oxide (CaO), silicon dioxide (SiO₂) and small amounts of aluminum oxide (Al₂O₃) and iron oxide (Fe₂O₃). Raw materials that provide these constituents are limestone, chalk and clay or limestone marl as its natural occurring mixture.

Gypsum/Anhydrite/Residual gypsum: 0 - 5 % Gypsum and anhydrite are added as setting regulators to cement. Many cement plants use residual gypsum from flue gas desulfurization as well.

This product contains substances listed in the *candidate list* (date: 20.11.2020) exceeding 0.1 percentage by mass: no

Reference service life

This study covers the production stage information (from A1 to A3) of the product. As no use stage is declared, the reference service life for cement is irrelevant.

LCA: Calculation rules

Declared Unit

The declared unit is 1 metric t of CEM I 52,5 R

Declared unit

Name	Value	Unit
Declared unit	1	t
Conversion factor to 1 kg	0.001	-

System boundary

Type of EPD: cradle-to-gate (A1-A3)

For the modelling of cement, both specific production data from HeidelbergCement and background data (especially for upstream processes) have been used. For life cycle modelling of the considered product, the verified Global Cement and Concrete Association GCCA online tool for EPDs of concrete and cement is used. The tool was developed by Quantis and is owned by the Global Cement and Concrete Association. The life cycle assessment in the tool has been implemented in compliance with EN 15804, the General Programme Instructions (GPI 2.5) for the International EPD® System, the product category rules The product category rules cover "concrete and concrete elements for building and civil engineering, excluding autoclaved aerated concrete", as stated in EN 16757 also clinker, cement and concrete. For the present study, version 2.5 of the GCCA tool was used, largely being based on the database ecoinvent v3.3. A significant factor regarding primary data collection is the emission measurement directly at the plant. In line

with the official regulations, regular data collections are established at HeidelbergCement group. The emission data of the clinker burning process are included in this LCA study. Preferably directly measured kiln emission values in the specific plant are considered. Noise, landscape impact, vibration etc. are not within the scope of this study. In case that specific kiln emission data are not available, default values are automatically used by the GCCA tool.

The selected system boundaries comprise the production of cement including raw material extraction up to the finished product at the factory gate.

The product stage contains:

Module A1: Extraction and processing of raw materials.

Module A2: Transport of raw materials to the factory gate and internal transport.

Module A3: Cement production.

The construction stage, the use stage and the disposal stage are not included in the life cycle assessment of cement.

Comparability

Basically, a comparison or an evaluation of EPD data is only possible if all the data sets to be compared were created according to *EN 15804* and the building context, respectively the product-specific characteristics of performance, are taken into account.

LCA: Scenarios and additional technical information

The development of scenarios has to be made on the finished product (e.g. concrete) and not on the upstream product cement.



_CA: Results

	DESCRIPTION OF THE SYSTEM BOUNDARY (X = INCLUDED IN LCA; MND = MODULE NOT DECLARED; MNR = MODULE NOT RELEVANT)															
	DUCT S		CONST	RUCTI	USE STAGE					EN	D OF LI	BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARIES				
Raw material supply	Transport	Manufacturing	Transport from the gate to the site	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse- Recovery- Recycling- potential
A1	A2	А3	A4	A 5	B1	B2	В3	B4	B5	В6	B7	C1	C2	C3	C4	D
X	Χ	Х	MND	MND	MND	MND	MNR	MNR	MNR	MND	MND	MND	MND	MND	MND	MND
RESU	RESULTS OF THE LCA - ENVIRONMENTAL IMPACT according to EN 15804+A1: 1 metric t CEM I 52,5R															
	Parameter Unit				A1-A3											
Donle	Global warming potential [kg CO ₂ -Eq.]					8.32E+2 9.93E-6										
Depletion potential of the stratospheric ozone layer [kg CFC11-Eq.]				4.1	9.93E-0											

Abiotic depletion potential for fossil resources [MJ] RESULTS OF THE LCA - INDICATORS TO DESCRIBE RESOURCE USE according to EN 15804+A1: 1 metric t CEM I 52.5R

[kg SO₂-Eq.]

[kg (PO₄)³-Eq.]

[kg ethene-Eq.]

[kg Sb-Eq.]

Parameter	Unit	A1-A3
Renewable primary energy as energy carrier	[MJ]	2.98E+2
Renewable primary energy resources as material utilization	[MJ]	0.00E+0
Total use of renewable primary energy resources	[MJ]	2.98E+2
Non-renewable primary energy as energy carrier	[MJ]	2.84E+3
Non-renewable primary energy as material utilization	[MJ]	0.00E+0
Total use of non-renewable primary energy resources	[MJ]	2.84E+3
Use of secondary material	[kg]	2.97E+1
Use of renewable secondary fuels	[MJ]	1.05E+3
Use of non-renewable secondary fuels	[MJ]	1.26E+3
Use of net fresh water	[m³]	8.61E+0

RESULTS OF THE LCA – WASTE CATEGORIES AND OUTPUT FLOWS according to EN 15804+A1: 1 metric t CEM I 52.5R

Parameter	Unit	A1-A3
Hazardous waste disposed	[kg]	IND
Non-hazardous waste disposed	[kg]	IND
Radioactive waste disposed	[kg]	IND
Components for re-use	[kg]	0.00E+0
Materials for recycling	[kg]	3.03E-1
Materials for energy recovery	[kg]	0.00E+0
Exported electrical energy	[MJ]	0.00E+0
Exported thermal energy	[MJ]	0.00E+0

Remark to Global warming potential:

Acidification potential of land and water

Eutrophication potential

Formation potential of tropospheric ozone photochemical

oxidants

Abiotic depletion potential for non-fossil resources

This includes 138.7 kg CO2-eq. from the incineration of wastes in clinker production. According to the polluterpays principle EN 15804 that would be assigned to the production system, which has caused the waste. In this EPD the CO2 contribution is not subtracted. This is to ensure comparability across countries of calculated global warming potentials for cements even if the used secondary fuels in other countries do not have waste status.

Remark to Waste categories:

The waste indicators account for wastes from clinker and cement manufacturing only.

References

IBU 2016

IBU (2016): General Programme Instructions for the Preparation of EPDs at the Institut Bauen und Umwelt e.V., Version 1.1 Institut Bauen und Umwelt e.V., Berlin. www.ibu-epd.de

ISO 14025

EN ISO 14025:2011-10, Environmental labels and declarations — Type III environmental declarations — Principles and procedures

1.41E+0

4.68E-1

1.14E-1

1.93E-4

2.19E+3



EN 15804

EN 15804:2012-04+A1 2013, Sustainability of construction works — Environmental Declarations — Core rules for the product category of construction products

EN 16757

EN 16757:2017, Sustainability of construction works - Environmental product declarations - Product Category Rules for concrete and concrete elements

Candidate List of Substances of Very High Concern for Authorisation

European Chemical Agency, 2019 www.echa.europa.eu/web/guest/candidate-list-table

ecoinvent v3.3

ecoinvent database, version 3.3, 2016 https://www.ecoinvent.org/

EN 197-1

EN 197-1:2011, Cement - part 1: Composition specification and conformity criteria for common cements

EN 206

EN 206:2013, Concrete: Specification, performance, production and conformity

(EU) No. 305/2011 (CPR)

Regulation (EU) No 305/2011 of the European Parliament and of the council of 9 March 2011 laying down harmonised conditions for the marketing of construction products and repealing Council Directive 89/106/EEC

General principles

for the EPD range of Institut Bauen und Umwelt e.V. (IBU), 2013-04 www.ibu-epd.com

General Programme Instructions

https://www.environdec.com/The-International-EPD-System/General-Programme-Instructions/

GCCA

Global Cement and Concrete Association https://gccassociation.org/ Online tool: https://concreteepd-tool.org/

PCR 2012:01

Product Category Rules according to ISO 14025: Construction products and construction services, version 2.01, 2012:01 http://environdec.com/en/PCR/Detail/?Pcr=8098

Quantis

https://quantis-intl.com/

UN CPC 3744 Cement

Product Category Rules for Cement, 2010, http://environdec.com/en/PCR/Detail/pcr2010-09

UN CPC 375 Concrete

Product Category Rules for Unreinforced Concrete, WBCSD Cement Sustainability Initiative, 2013 http://environdec.com/en/PCR/Detail/pcr2013-02



Publisher

Germany

Institut Bauen und Umwelt e.V. Panoramastr. 1 10178 Berlin Tel +49 (0 Fax +49 (0 Mail info@ Web **www.**

Tel

Fax

Mail

Web

+49 (0)30 3087748- 0 +49 (0)30 3087748- 29 info@ibu-epd.com www.ibu-epd.com



Programme holder

Institut Bauen und Umwelt e.V. Panoramastr 1 10178 Berlin Germany Tel +49 (0)30 - 3087748- 0 Fax +49 (0)30 - 3087748 - 29 Mail info@ibu-epd.com Web **www.ibu-epd.com**



Author of the Life Cycle Assessment

Global Cement and Concrete Association Kingdom Street 2 W2 6JP London United Kingdom +442035804268 +442035804268

info@gccassociation.org
gccassociation.org



Owner of the Declaration

AS Kunda Nordic Tsement Jaama 2 33106 Kunda Estonia Tel +3723229900 Fax +3723221646 Mail knc@knc.ee Web **www.knc.ee**